



KBJ Hydraulic Pump Technology Co., Ltd.

7SRS9XMUUC1+[32-1000/1]LM THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 7SRS9XMUUC1+[32-1000/1]LM

7SRS9XMUUC1+[32-1000/1]LM Bearing 2D drawings
and 3D CAD models

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	7
Nominal Part Number	9
Rail Type	Standard
Rail Width W1	9 mm
Mounting Height M	10 mm
Rail Length L	32 ~ 1000 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2690
Basic Load Rating Static Rating Co(N)	2750
Allowable Static Moment MA(N m)	9.31
Allowable Static Moment MB(N m)	10.7
Allowable Static Moment MC(N m)	12.7
Symbols for Dust Resistance	UU: End Seals (Best Leadtime)
Block external dimension W	20 mm
Block external dimension L	30.8 mm



KBJ Hydraulic Pump Technology Co., Ltd.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	19.8 mm