



# KBJ Hydraulic Pump Technology Co., Ltd.

## 9SRS7WGS+[33-300/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 9SRS7WGS+[33-300/1]LM

9SRS7WGS+[33-300/1]LM Bearing 2D drawings and 3D CAD models

Days to Ship	27 Days
Block Type	[Short] S: Short
The number of LM blocks combined with a axis	9
Nominal Part Number	7W
Rail Type	Wide Rail
Rail Width W1	14 mm
Mounting Height M	9 mm
Rail Length L	33 ~ 300 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	1060
Basic Load Rating Static Rating Co(N)	1350
Allowable Static Moment MA(N m)	2.58
Allowable Static Moment MB(N m)	2.96
Allowable Static Moment MC(N m)	9.95
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	25 mm
Block external dimension L	22.5 mm



## KBJ Hydraulic Pump Technology Co., Ltd.

Number of Block Mounting Holes(holes)	2
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	11.9 mm