



KBJ Hydraulic Pump Technology Co., Ltd.

9SRS15WN+[76-900/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 9SRS15WN+[76-900/1]L[H,P]M

9SRS15WN+[76-900/1]L[H,P]M Bearing 2D
drawings and 3D CAD models

Days to Ship	22 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	9
Nominal Part Number	15W
Rail Type	Wide Rail
Rail Width W1	42 mm
Mounting Height M	16 mm
Rail Length L	76 ~ 900 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	12400
Basic Load Rating Static Rating Co(N)	12100
Allowable Static Moment MA(N m)	106
Allowable Static Moment MB(N m)	106
Allowable Static Moment MC(N m)	250
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	60 mm
Block external dimension L	74.5 mm
Number of Block Mounting	4



KBJ Hydraulic Pump Technology Co., Ltd.

Holes(holes)	
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	4.5 mm
Block dimension L1	57.9 mm